

# IP MICROPHONE

## DESCRIPTION

- 8 or 15 keys microphone console to broadcast live or delayed messages: keypad with capacitive keys (each key corresponds to a zone and is equipped with a green LED to indicate the selection of the zone).
- 3 push-buttons to record (record with replay), to broadcast live or delayed.
- Built-in loud-speaker to listen to the message before broadcast.
- "Jingle" before broadcast of the message.
- Archiving of voice messages. A filed message can be used in a step of a program.
- Supervision: SNMP v1 and v2c.

## STANDARDS

- Applicable standards: EN 60950 - EN 55022 - EN 55024 - EN 62311.



## ELECTRICAL FEATURES

- **Power supply**..... PoE (Power over Ethernet).
- **Consumption**..... 8 W.
- **Sensitivity**..... -58dB  $\pm$ 2dB.
- **Number of keys**..... 8 or 15.

## MECHANICAL FEATURES

- **Construction**..... LCD screen with 2 lines of characters:
  - Character size: 5 mm.
  - White characters on blue background.
  - Maximum number of characters per lines: 12.
- **Operating temperature range**..... 0° to +50°C.
- **Protection index**..... IP31, IK06.
- **Weight**..... 450 g.
- **Dimensions of the base**..... L198 x H34/23 x D167 mm.
- **Gooseneck length (including the microphone)** 330 mm.

## REFERENCES

- 907 755..... Harmonys microphone - 8 keys
- 907 756..... Harmonys microphone - 15 keys



Dimensions in mm

